


REPLACE THE FUSE

Most often, fuses blow because too many sets have been strung end-to-end. Please do not string together more than three(3) miniature bulb light sets.

- Before changing fuses, make sure the set is unplugged. Grasp plug and remove from the receptacle or other outlet device. Do not unplug by pulling on cord.
- Open fuse cover. Slide open fuse access cover on top of attachment plug towards blades.(see diagram)
- Remove fuses carefully. Turn plug over to empty fuse compartment.
- Risk of fire. Replace fuses only with 3 Amp, 125 Volt fuses that are included in this set.
- Close fuse cover. Make sure the fuses are being properly seated in the fuse holder then push the fuse access door all the way back to completely cover the fuse holder.
- Risk of fire. Do not replace attachment plug. Contains a safety device (fuse) that should not be removed. Discard product if the attachment plug is damaged.



CAUTION:

To reduce the risk of overheating, replace burned-out lamps promptly. Use 3.5 volt, 0.42 watt lamps only.

DIRECTIONS

Always test your light set before decorating. Make sure that all bulbs are firmly in their sockets. Never twist bulbs since this can cause part of the set to go out. If a bulb burns out, replace it promptly to prolong the life of other bulbs.(See bulb replacement instructions).

ATTENTIONS: Due to the nature of the material used, loss of some debris material during shipment and assembly is to be Please dispose of debris and keep out of reach of children. Its beauty will not be diminished by the amount of debris.

FOR INDOOR AND OUTDOOR USE

120V 60Hz 0.24A

MODEL NO.: L13062-C

UL FILE NO.: E329250

MADE IN CHINA

ASSEMBLY DIAGRAM

PACKAGE CONTENTS

Part	Description	Quantity
A	Hair	1 PCS
B	Body	1 PCS
C	Hand (Left)	1 PCS
D	Hand (Right)	1 PCS
E	Wing (Left)	1 PCS
F	Wing (Right)	1 PCS
G	Skirt (Upper Half)	1 PCS
H	Skirt (Half Bottom)	1 PCS

REPLACEMENT PARTS LIST

Description	Quantity
Spare bulb	4 pcs
Fuse	2 pcs
Plastic ties	10 pcs
Ground stakes	4 pcs
Safety Pin	2 pcs

ASSEMBLY INSTRUCTION

Step 1: Assembly Upper Half Skirt(G) and Half Bottom Skirt(H), on the Skirt(G) have a hook, use the hook hook Skirt(H) then push downward assembly Skirt(G) on Skirt(H).

Step 2: Assembly Body(B) and Skirt(G), on the navel position have a hook, use the hook hook Skirt(G) then push downward assembly Body(B) on the Skirt(G).

Step 3: Find the corresponding position Push downward assembly two hands (C&D) on the body (B)

